



Lindner Hinged Door Swing MOP

Description

Lindner hinged doors are suitable for a variety of applications. Originally developed for use in GMP-cleanrooms, they also provide outstanding services in all kinds of areas with the highest hygiene requirements and are tailored in detail to these areas of application. The flexible design makes it possible to implement a radiation protection variant for operating rooms or X-ray rooms without optical modifications.

The Lindner Swing MOP door can be implemented as a complete package with automatic drive, lock control, holding magnet or other electrical components. Whether for simple manual use, automated or as a complex system integrated into airlock controls - the options are almost limitless. The door leaf has a thickness of 40 mm and the door gap is 3 – 4 mm.

Specialized solutions can be implemented for specific projects at any time.

Fields of application

- Operating theatres
- Intensive care units
- Laboratories



For further information please visit
www.Lindner-Group.com

Lindner SE | Reinraumtechnik, Bahnhofstraße 29, 94424 Amstorf / Germany, Tel. +49 (0)8723/20-0, Reinraumtechnik@Lindner-Group.com, www.Lindner-Group.com

1. Door leaf

Number of door leaves	<ul style="list-style-type: none"> • Single-leaf door • Double-leaf door
-----------------------	--

1.1 Metal door leaf (with particle board core)

Material of outer shell	<ul style="list-style-type: none"> • Frame: - galvanized sheet steel - Stainless steel - Aluminum • Glazing: TSG, LSG, insulated glazing
-------------------------	--

Frame	<ul style="list-style-type: none"> • Powder coated RAL 9010 • Powder coated according to RAL • Powder coated according to NCS • Stainless steel double-cut (sanded and brushed) • Stainless steel 240 grit sanded
-------	--

1.2 Built-in components / Extensions

Handle options	<ul style="list-style-type: none"> • Knob / Knob • Handle / Knob • Handle / Handle
----------------	---

Hinges	<ul style="list-style-type: none"> • VX – hinges • Hidden hinges
--------	--

Main locks	<ul style="list-style-type: none"> • Mortise lock class 4 • Panic mortise lock • Profile cylinder
------------	--

Door sealing (optional)	<ul style="list-style-type: none"> • Frame sealing • Floor sealing
-------------------------	--

Glazing (optional)	<ul style="list-style-type: none"> • Without blind / roller blind • With internal electric blind • With internal manual blind • With internal electric roller blind
--------------------	---

Installation variants of glazing	<ul style="list-style-type: none"> • Flush installation without covering frame • With surface mounted covering frame
----------------------------------	--

Special glazing (optional)	<ul style="list-style-type: none"> • Radiation protection • Laser protection
----------------------------	--

Additional hardware	<ul style="list-style-type: none"> • Additional locks • Reed switches • Electric opener • Strike plate • Scratch protection
---------------------	--



For further information please visit
www.Lindner-Group.com

Lindner SE | Reinraumtechnik, Bahnhofstraße 29, 94424 Amstorf / Germany, Tel. +49 (0)8723/20-0, Reinraumtechnik@Lindner-Group.com, www.Lindner-Group.com

We reserve the right to adapt and amend all details and information at any time. We do not accept liability for information that is inadvertently incorrect. This document is protected by copyright law. Processing, unauthorised use or reproduction and public distribution are not permitted. Reproduction and distribution to third parties are only permitted with our express consent.

2. Frame

Material	<ul style="list-style-type: none"> Galvanized steel Stainless steel
Surface	<ul style="list-style-type: none"> Powder coated RAL 9010 Powder coated according to RAL Powder coated according to NCS Stainless steel double-cut (sanded and brushed) Stainless steel 240 grit sanded
Controls	<ul style="list-style-type: none"> Operation button ¹⁾ (<i>permanent on, person-, bed passage</i>) Rubber pad operation button on the frame ¹⁾ Pad switch ¹⁾ Non-contact controls ¹⁾ (<i>integrated in the adjacent wall</i>)
Controls / Signals (optional)	<ul style="list-style-type: none"> Button for operating the integrated electric blinds and roller blinds Emergency button (for interlocking) Traffic light LED-RGB (for interlocking)
Specials (optional)	<ul style="list-style-type: none"> Radiation protection

1) Only available with automatic drives.

3. Door Drive / Door Closer

Door closer	<ul style="list-style-type: none"> Integrated door closer Overhead door closer
Drive type	<ul style="list-style-type: none"> Automatic door drive according to DIN EN 16005 / DIN 18650
Special function (optional)	<ul style="list-style-type: none"> Airlock function according to requirement

4. Safety Precautions

Sensors (optional)	Door movement monitoring according to DIN 18650 and DIN EN 16005
Door leaf monitoring	Electronic monitoring of dynamic force limitation when opening and closing; the door stops and remains stopping as soon as the allowable resistance is exceeded.

5. Performance

Fire protection	T0
Sound insulation	Up to 35 dB Rw acc. to DIN EN 20140-3 (ISO 140-3: 1995)* *only for single leaf doors



For further information please visit
www.Lindner-Group.com

Lindner SE | Reinraumtechnik, Bahnhofstraße 29, 94424 Amstorf / Germany, Tel. +49 (0)8723/20-0, Reinraumtechnik@Lindner-Group.com, www.Lindner-Group.com