



## Trox L-KU-K30

### Fire Damper

Different ventilation components of Trox can be integrated into LMD fire rated metal ceilings. The required cut-outs in the ceiling elements are adapted to these ventilation components.

- Integration of Trox ventilation components possible
- Cut-out in ceiling element adapted to ventilation components

### Technical Details

---

#### Trox Fire Damper L-KU-K30/300x160

nominal size: 300 x 300 mm  
connection size: Ø 160 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 362 mm  
2 custom-fit panels: 179.5 mm

#### Trox Fire Damper L-KU-K30/400x160

nominal size: 400 x 400 mm  
connection size: Ø 160 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 462 mm  
2 custom-fit panels: 229.5 mm

#### Trox Fire Damper L-KU-K30/400x200

nominal size: 400 x 400 mm  
connection size: Ø 200 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 462 mm  
2 custom-fit panels: 229.5 mm

#### Trox Fire Damper L-KU-K30/500x160

nominal size: 500 x 500 mm  
connection size: Ø 160 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 562 mm  
2 custom-fit panels: 279.5 mm

#### Trox Fire Damper L-KU-K30/500x200

nominal size: 500 x 500 mm  
connection size: Ø 200 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 562 mm  
2 custom-fit panels: 279.5 mm



### **Trox Fire Damper L-KU-K30/500x250**

nominal size: 500 x 500 mm  
connection size: Ø 250 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 562 mm  
2 custom-fit panels: 279.5 mm

### **Trox Fire Damper L-KU-K30/600x160**

nominal size: 600 x 600 mm  
connection size: Ø 160 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 662 mm  
2 custom-fit panels: 329.5 mm

### **Trox Fire Damper L-KU-K30/600x200**

nominal size: 600 x 600 mm  
connection size: Ø 200 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 662 mm  
2 custom-fit panels: 329.5 mm

### **Trox Fire Damper L-KU-K30/600x250**

nominal size: 600 x 600 mm  
connection size: Ø 250 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 662 mm  
2 custom-fit panels: 329.5 mm

### **Trox Fire Damper L-KU-K30/600x315**

nominal size: 600 x 600 mm  
connection size: Ø 315 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 662 mm  
2 custom-fit panels: 329.5 mm

### **Trox Fire Damper L-KU-K30/625x160**

nominal size: 625 x 625 mm  
connection size: Ø 160 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 687 mm  
2 custom-fit panels: 342 mm

### **Trox Fire Damper L-KU-K30/625x200**

nominal size: 625 x 625 mm  
connection size: Ø 200 mm



---

max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 687 mm  
2 custom-fit panels: 342 mm

#### **Trox Fire Damper L-KU-K30/625x250**

nominal size: 625 x 625 mm  
connection size: Ø 250 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 687 mm  
2 custom-fit panels: 342 mm

#### **Trox Fire Damper L-KU-K30/625x315**

nominal size: 625 x 625 mm  
connection size: Ø 315 mm  
max. corridor width: 2.300 mm  
width of custom-fit panel at 3 mm joint (depending on system):  
1 custom-fit panel: 687 mm  
2 custom-fit panels: 342 mm