

Fittings Distribution system

Product description

Different fittings such as system distributors are available in the distribution system that is perfectly adapted to Plafotherm[®] heated/chilled ceilings. Various combination options offer you the possibility to expand the distributor to up to ten outlets.

- perfectly adapted to Plafotherm[®] heated/chilled ceilings
- · expansion of the distribution system to up to ten outlets



Project solutions

This product data sheet refers to the standard version of the product mentioned above. We would be happy to work with you to find the right solution for your project. Adapted to your building project, you will receive a perfectly matched system. Project-specific constructions and adaptations can be found in the offer documents.

Table of types

System distributor		n Î
Dimension	1⁄2" external/internal thread x 3* MQC 12 mm	With the second second
Material	brass	
Y-system distr	ibutor	
Dimension	¹ ⁄ ₂ " external thread x 2* MQC 12 mm	
Material	brass	
Y-system distributor		
Dimension	18 mm x 2* MQC 12 mm	5
Material	brass	
Screw-in pipe	end	
Dimension	½" external thread x 1* MQC 12 mm	
Material	brass	
Double nipple		
Dimension	2* MQC 12 mm	
Material	brass (alternative copper or stainless steel)	

We reserve the right to adapt and amend all details and information at any time. We do not accept liability for information that is inadvertently incorrect. Dimensional tolerances are permissible in compliance with the applicable standards. This document is protected by copyright law. Processing, unauthorised use or reproduction and public distribution are not permitted. Reproduction and distribution to third parties are only permitted with our express consent.



🗶 Lindner



]		
12 mm x 1* MQC 12 mm		
brass		
I		
15 mm x 1* MQC 12 mm		
brass		
$\frac{1}{2}$ x $\frac{3}{4}$ x $\frac{1}{2}$ internal thread		
brass		
]		•
12 mm x 1* MQC 12 mm		
copper		
elf-sealing		
1⁄2" external thread		
brass, nickel-plated		
12 mm		
brass		
	'	
l class		
class	DIN EN 13501-1	A1
	brass 15 mm x 1* MQC 12 mm brass 1/2" x ³ /4" x ¹ /2" internal thread brass 12 mm x 1* MQC 12 mm copper elf-sealing 1/2" external thread brass, nickel-plated 12 mm	brass 15 mm x 1* MQC 12 mm brass ½" x ¾" x ½" internal thread brass 12 mm x 1* MQC 12 mm copper elf-sealing ½" external thread brass, nickel-plated 12 mm brass

Heated and chilled ceilings

Plafotherm[®] B 100 Plafotherm[®] B 100 SD Plafotherm[®] B 110 Plafotherm[®] B 147 SD Plafotherm[®] E 200 Plafotherm[®] E 210 Plafotherm[®] E 213 Plafotherm[®] E 214 Plafotherm[®] E 312 Plafotherm[®] DS 315 Plafotherm® DS 320 Plafotherm® L 608 Plafotherm® L 609 Plafotherm® St 213 Plafotherm® KN Plafotherm® KN eco Plafotherm® GK HEKDA® Plafotherm® DS TAS Plafotherm® B/E AirHybrid Plafotherm® DS AirHybrid

Applications









2|2 Lindner SE | Heated and Chilled Ceilings Bahnhofstraße 29 | 94424 Arnstorf | Germany Phone +49 8723 20-3680 heating.cooling@Lindner-Group.com | www.Lindner-Group.com

We reserve the right to adapt and amend all details and information at any time. We do not accept liability for information that is inadvertently incorrect. Dimensional tolerances are permissible in compliance with the applicable standards. This document is protected by copyright law. Processing, unauthorised use or reproduction and public distribution are not permitted. Reproduction and distribution to third parties are only permitted with our express consent.