



Round wall or ceiling luminaire for surface mounting, equipped with LED technology.

Housing is made of sheet steel, colour acc. to RAL 9016.

Soft ceiling illumination is made by a circumferential indirect light.

Light is distributed via a frameless opal acrylic cover.

Electrical connection area on back side is slightly stepped (height: 22 mm).

Type	Lumen Output	System Power	Dimension (Ø x h)
FLAT C RL 300 1.5 OS	1.760 Lumen	15 Watt	300 x 75 (53+22) mm
FLAT C RL 360 3.5 OS	3.520 Lumen	30 Watt	360 x 75 (53+22) mm
FLAT C RL 470 4.0 OS	4.210 Lumen	36 Watt	470 x 75 (53+22) mm
FLAT C RL 600 5.5 OS	5.600 Lumen	48 Watt	600 x 75 (53+22) mm
FLAT C RL 900 8.0 OS	8.460 Lumen	57 Watt	900 x 75 (53+22) mm
FLAT C RL 1200 12.0 OS	12.180 Lumen	84 Watt	1.200 x 75 (53+22) mm

Technical Data:

Voltage: 220-240 V / 50-60 Hz
 Protection class: 1
 Protection type: IP20
 Ballast: switchable
 Cover: opal
 Colour: RAL 9016
 Light colour: 4.000K
 Colour Rendering: RA>80

Options:

Ballast DALI dimmable
 Housing acc. to RAL card
 Light colour 3.000K

Dimension Drawing:

