

Surface luminaire, equipped with LED technology.

Housing is made of aluminium, powder coated according to RAL colour chart.

Light is distributed via an opal acrylic diffuser, optionally via a microprismatic cover for offices (UGR<19).

According to customer requirements, light strips or light figures are possible on request.



Type	Lumen	System Power	Dimension (l x w x h)
PL 2 - 853 opal	3.100 Lumen	23 Watt	853 x 61 x 83 mm
PL 2 - 1133 opal	4.100 Lumen	32 Watt	1.133 x 61 x 83 mm
PL 2 - 1413 opal	5.000 Lumen	40 Watt	1.413 x 61 x 83 mm
PL 2 - 1693 opal	6.150 Lumen	48 Watt	1.693 x 61 x 83 mm
PL 2 - 853 opal HE	1.800 Lumen	14 Watt	853 x 61 x 83 mm
PL 2 - 1133 opal HE	2.300 Lumen	18 Watt	1.133 x 61 x 83 mm
PL 2 - 1413 opal HE	3.050 Lumen	23 Watt	1.413 x 61 x 83 mm
PL 2 - 1693 opal HE	3.550 Lumen	26 Watt	1.693 x 61 x 83 mm

Technical Information:

Voltage:	220-240 V / 50-60 Hz
Protection Class:	1
Protection Type:	IP 20
Ballast:	switchable
Cover:	opal
Colour:	RAL colour chart
Light Colour:	4.000K
CRI:	RA>80

Options:

- Light Colour 3.000K
- Housing Colour acc. to RAL Card
- Dimmable DALI
- Microprismatic cover UGR < 19 (e.g. type PL 2 mprm)
- Version Wallwasher

Dimension Drawing:

