



Vandal-proof luminaire for fire protection metal ceilings, equipped with LED technology.

The luminaire is suitable for integration into a fire protection metal ceiling panel (on-site).

Light is distributed via an impact-resistant opal cover made of polycarbonate.

The special screw fitting ensures protection against unauthorized opening.

Type	Lumen Output	System Power	Dimension (l x w x h)
T38 7++ 625 1.5 OS	1.540 Lumen	14 Watt	625 x 200 x 38 mm
T38 7++ 925 2.0 OS	2.310 Lumen	21 Watt	925 x 200 x 38 mm
T38 7++ 1225 3.0 OS	3.080 Lumen	28 Watt	1.225 x 200 x 38 mm
T38 7++ 1525 3.5 OS	3.850 Lumen	35 Watt	1.525 x 200 x 38 mm

### Technical Information:

Voltage:	220-240 V / 50-60 Hz
Protection Class:	1
Protection Type:	IP20
Ballast:	switchable
Cover:	opal, impact-resistant polycarbonate
Colour:	RAL 9016
Light Colour:	4.000K
CRI:	RA>80

### Options:

- Light Colour 3.000K
- Ballast DALI dimmable
- incl. preassembled connection cable, plug and connector
- Housing colour acc. to RAL card

### Dimension Drawing:

